


LED module

AS-2

AXS-2 is a compact 2-diode LED module, ideal for illuminating shallow signs and advertising forms. Thanks to its precise light distribution, it guarantees even illumination over the entire surface, even in structures with limited depth.

Scale 1:1



Dual LED design

The module equipped with two LEDs provides optimal brightness and even illumination, ideal for shallow advertising forms.

Ideal for shallow advertising forms

Dedicated to shallow sign applications where even illumination with limited design depth is crucial.

IP65 waterproof

Protection against moisture, dust and changing weather conditions makes the module suitable for both indoor and outdoor applications.

Technical specifications

Packing: 500 (10 x 50)

Model	Product code	LED type	Voltage	Power	CRI	Colour temp.	Beam angle	Luminous flux	Module spacing	Max pcs/chain
AS-2	01-001-011-01-	2 x 2835 SMD	12 V DC	0.32 W	75	9000-9500 K	120°	20 lm	40 mm	≤50
AS-2	01-001-011-02-	2 x 2835 SMD	12 V DC	0.32 W	75	3000-3500 K	120°	18 lm	40 mm	≤50
AS-2	01-001-011-03-	2 x 2835 SMD	12 V DC	0.32 W	75	6500-7000 K	120°	20 lm	40 mm	≤50
AS-2	01-001-011-05-	2 x 2835 SMD	12 V DC	0.32 W	-	620-630 nm	120°	-	40 mm	≤50
AS-2	01-001-011-06-	2 x 2835 SMD	12 V DC	0.32 W	-	520-530 nm	120°	-	40 mm	≤50
AS-2	01-001-011-07-	2 x 2835 SMD	12 V DC	0.32 W	-	460-470 nm	120°	-	40 mm	≤50
AS-2	01-001-011-10-	2 x 2835 SMD	12 V DC	0.32 W	-	588-595 nm	120°	-	40 mm	≤50
AS-2	01-001-011-11-	2 x 3528 SMD	12 V DC	0.32 W	-	455-457.5 nm	120°	-	40 mm	≤50