

Power supply

Electra

Electra is a series of fixed-voltage mounting power supplies that combine compact dimensions, high quality and an attractive price. With a wide power range to choose from and a high IP67 protection rating, these power supplies are the perfect solution for a variety of lighting applications, both indoor and outdoor.



Wide wattage range

Allows customisation to suit different needs and applications.

High IP67 protection

Ensures reliability in harsh environments, protecting against dust and moisture.

Compact dimensions

Ideal for installation in confined spaces.

Technical specifications

Model	Product code	Input voltage	Output voltage	Output current	Operating temp.	Frequency	Power	Dimensions	Weight	* Prot.
Electra 512	01-009-004-12-05	170~250 V AC	12 V DC	0.417 A	-30~50°C	50~60 Hz	5 W	52 x 26 x 21 mm	0.042 kg	● ●
Electra 1512	01-009-004-12-15	170~250 V AC	12 V DC	1.25 A	-30~50°C	50~60 Hz	15 W	162 x 28 x 20 mm	0.17 kg	● ●
Electra 3612	01-009-004-12-36	170~250 V AC	12 V DC	3.0 A	-25~50°C	50~60 Hz	36 W	148 x 40 x 30 mm	0.280 kg	● ●
Electra 3624	01-009-004-24-36	170~250 V AC	24 V DC	1.5 A	-25~50°C	50~60 Hz	36 W	148 x 40 x 30 mm	0.280 kg	● ●
Electra 6012	01-009-004-12-60	170~250 V AC	12 V DC	5.0 A	-25~50°C	50~60 Hz	60 W	166 x 42 x 34 mm	0.39 kg	● ●
Electra 6024	01-009-004-24-60	170~250 V AC	24 V DC	2.5 A	-25~50°C	50~60 Hz	60 W	166 x 42 x 34 mm	0.39 kg	● ●
Electra 10012	01-009-004-12-100	170~250 V AC	12 V DC	8.33 A	-25~50°C	50~60 Hz	100 W	190 x 52 x 37 mm	0.640 kg	● ●
Electra 10024	01-009-004-24-100	170~250 V AC	24 V DC	4.16 A	-25~50°C	50~60 Hz	100 W	190 x 52 x 37 mm	0.640 kg	● ●
Electra 15012	01-009-004-12-150	170~250 V AC	12 V DC	12.5 A	-25~50°C	50~60 Hz	150 W	190 x 63 x 38 mm	0.720 kg	● ●
Electra 15024	01-009-004-24-150	170~250 V AC	24 V DC	6.5 A	-25~50°C	50~60 Hz	150 W	190 x 63 x 38 mm	0.720 kg	● ●

* Protections

- Short-circuit protection
- Overload protection
- Over voltage protection
- Over temp. protection